

adorn

LAMINATES

Technical Data Sheet


	Classic	Select	3D	3D LUX
Thickness	12mm	10mm	12mm	12mm
Board Size (mm)	1215 x 197	1845 x 235	2265 x 235	2265 x 235
Decorative Layer	Matte Finish	Textured Matte	3D Print Matte	3D Print Matte
Water Resistance	Up to 12 hours	Surface Waterproof	Up to 72 hours	Surface Waterproof
Abrasion Rating	AC4	AC5	AC4	AC5
Repeat Patterns	6 planks	8 planks	up to 50 planks	up to 50 planks
Sqm/ Box	1.915m ²	2.602m ²	2.129m ²	2.129m ²
Pieces / Box	8	6	4	4
Weight / Box	20kg	22.5kg	22kg	22kg
Box / Pallet	50	80 / 64	80 / 57	80 / 57

Product Summary

Board Type	Plank
Wear Layer	UV Protected Aluminium Oxide Melamine
Core Structure	High Density Fibreboard
Backing Layer	Moisture Resistant Melamine Paper
Edge Profile	Micro Bevelled
Clicking System	Uniclic (Patent Unilin)
Installation Method	Floating Only
Slip Resistance	P2 / D1
Fire Tested	AS ISO 9239.1-2003
Subfloor	Maximum of 3mm undulations
Durability	Water resistant construction, stain & scratch resistance, hard wearing
Suitable Application	Residential & Commercial



Warranty



NATIONAL SELECT
FLOORS

02 7229 7323

info@nationalselectfloors.com.au

Building B/6 Carter Street, Lidcombe NSW 2141

www.nationalselectfloors.com.au