



SPECIFICATION DATA SHEET

The 15mm range represents the pinnacle of our Lamella Engineered Timbers. A statement of scale, sophistication, and timeless appeal, this larger format creates a seamless flow through interior spaces, enhancing natural light and delivering a sense of grandeur that elevates any design.

Expertly engineered with a 15 mm construction, this range combines architectural presence with enduring stability. The matte brushed finish highlights the natural character of European Oak, while advanced UV cured lacquer layers protect against everyday stains and fading. The result is a floor that retains its flawless appearance with minimal upkeep, year after year.

Offered in an exclusive palette of contemporary décors, the 15mm range embodies premium craftsmanship, exceptional durability, and accessible luxury; designed to transform living spaces into refined environments.

Product Details

Style	Plank
Timber Origins	European Oak
Thickness / Wear Layer	15 / 4 mm
Board Size	2200 x 260 mm
Edge Profile	Micro Bevelled
Fitting System	Tongue & Groove
Installation Method	Floating Glue Down Nail


Sqm/ Box	2.288 m ²
Pieces / Box	6 rows includes <20% nested
Box / Pallet	50
Weight / Box	28.5 kg

Suitable Application	Residential & Commercial
-----------------------------	--------------------------

Performance & Safety Testing

Slip (AS 4586-2013)	P3 (SRV 39)
Fire (AS ISO 9239.1-2003)	3.9 kW/m ²
Acoustic Outcome	L'nTw 40 (Homestead 5 mm rubber)
AAAC Rating	6 Star

Reports are available upon request.



Serein
LET-1501




Wyn
LET-1502



Auer
LET-1503



Caldu
LET-1504



Fika
LET-1505




Maes
LET-1506



Laine
LET-1507



Ricci
LET-1508



Toska
LET-1509



Kohle
LET-1510

Images are for general illustration only. Actual product colours may differ due to variations in screen displays or printing processes. The scale of the images does not reflect true colour variation. For an accurate representation, please refer to physical samples. Images are not legally binding.

Technical Summary

Grading	Natural Grade
Top Layer	UV Cured Polyurethane Aluminium Oxide Coating
Surface	Pre-finished Matte Lacquer
Finish	Light Wire Brushed Texture
Core Structure	Plantation Eucalyptus/Birch Multi Cross Plywood
Backing Layer	Birchwood Veneer for extra stability
Topcoat Adhesion	4B ASTM D3359
Wear Resistance	≥500 circles (S33 sand paper) ASTM D4060
Moisture Content	6-9%
Gloss Level	6-8°
Density	754 kg/m ³
Janka Hardness Rating	5.5-6.0 kN
Formaldehyde Emission	CARB Phase One ≤0.08 ppm ASTM E1333
Environmental	Sourced from sustainable managed resources



Durability

7 coats
UV-hardened
surface finish,
consisting of
polyurethane
and aluminum
oxide

Wearability

4 mm top
layer in solid wood.

Stability

Multiple cross
plywood layers.



This specification data sheet has been prepared by National Select Floors. All information provided was accurate at the time of writing and publication. National Select Floors reserves the right to alter product details at any time without prior notification. Images included are for illustrative purposes only and do not confer any rights or guarantees.

National Select Floors recommends installation by a professional flooring contractor or skilled tradesperson and must follow the Australian Standards for flooring installations. All installations must also be performed in accordance with National Select Floors installation guidelines. If you have any concerns regarding the installation process, please contact your reseller.

Installation guidelines and Warranty information are available from our website.