

SPECIFICATION DATA SHEET

The Natives range is a tribute to the enduring beauty of Australian hardwoods, engineered to embody timeless luxury with an understated elegance that lasts for generations. Featuring a 3 mm premium wear layer of authentic native species, it captures the classic appeal of natural timber while delivering exceptional durability.

Sustainably sourced from Australia's finest hardwoods, each plank radiates warmth, character, and strength, ensuring a product that is as responsible as it is refined.

The subtle matte brushing enhances the natural grain and texture, while multiple layers of UV cured lacquer provide advanced protection against stains and fading. Designed for longevity with minimal upkeep, the Natives range offers a floor that will remain as elegant and flawless as the day it was laid.

Product Details

Style	Plank
Timber Origins	Australian Species
Thickness / Wear Layer	15 / 3 mm
Board Size	A: 1900 x 190 mm B: 1900 x 136 mm
Edge Profile	Micro Bevelled
Fitting System	Tongue & Groove
Installation Method	Floating Glue Down Nail
Suitable Application	Residential & Commercial
Sqm/ Box	A: 2.166 m ² B: 1.551 m ²
Pieces / Box	6 rows includes <20% nested
Box / Pallet	50
Weight / Box	A: 21.12 kg B: 15.12kg

Performance & Safety Testing

Slip (AS 4586-2013)	P3 (SRV 36)
Fire (AS ISO 9239.1-2003)	3 kW/m ²
Acoustic Outcome	L'nTw 38 (Homestead 5 mm rubber)
AAAC Rating	6 Star

Reports are available upon request.



Blackbutt

LET-1511 (A) | LET-1513 (B)



Spotted Gum

LET-1512 (A) | LET-1514 (B)

Images are for general illustration only. Actual product colours may differ due to variations in screen displays or printing processes. The scale of the images does not reflect true colour variation. For an accurate representation, please refer to physical samples. Images are not legally binding.

Technical Summary

Grading	Select Grade
Top Layer	UV Cured Polyurethane Aluminium Oxide Coating
Surface	Pre-finished Matte Lacquer
Finish	Brushed Texture
Core Structure	Plantation Eucalyptus/Birch Multi Cross Plywood
Backing Layer	Birchwood Veneer for extra stability
Topcoat Adhesion	4B ASTM D3359
Wear Resistance	≥550 cycles (S33 sand paper) ASTM D4060
Moisture Content	6-9%
Gloss Level	6-8°
Density	750 kg/m ³
Janka Hardness Rating	Blackbutt: 9.1-9.3 kN Spotted Gum: 11.0 kN
Formaldehyde Emission	CARB Phase One ≤0.08 ppm ASTM E1333
Environmental	Sourced from sustainable managed resources

Durability

7 coats
UV-hardened
surface finish,
consisting of
polyurethane
and aluminum
oxide

Wearability

3 mm top
layer in solid wood.

Stability

Multiple cross
plywood layers.



This specification data sheet has been prepared by National Select Floors. All information provided was accurate at the time of writing and publication. National Select Floors reserves the right to alter product details at any time without prior notification. Images included are for illustrative purposes only and do not confer any rights or guarantees.

National Select Floors recommends installation by a professional flooring contractor or skilled tradesperson and must follow the Australian Standards for flooring installations. All installations must also be performed in accordance with National Select Floors installation guidelines. If you have any concerns regarding the installation process, please contact your reseller.

Installation guidelines and Warranty information are available from our website.