



## SPECIFICATION DATA SHEET

The 15mm range represents the pinnacle of our Lamella Engineered Timbers. A statement of scale, sophistication, and timeless appeal, this larger format creates a seamless flow through interior spaces, enhancing natural light and delivering a sense of grandeur that elevates any design.

Expertly engineered with a 15 mm construction, this range combines architectural presence with enduring stability. The matte brushed finish highlights the natural character of European Oak, while advanced UV cured lacquer layers protect against everyday stains and fading. The result is a floor that retains its flawless appearance with minimal upkeep, year after year.

Offered in an exclusive palette of contemporary décors, the 15mm range embodies premium craftsmanship, exceptional durability, and accessible luxury; designed to transform living spaces into refined environments.

### Product Details

<b>Style</b>	Plank
<b>Timber Origins</b>	European Oak
<b>Thickness / Wear Layer</b>	15 / 4 mm
<b>Board Size</b>	2200 x 260 mm
<b>Edge Profile</b>	Micro Bevelled
<b>Fitting System</b>	Tongue & Groove
<b>Installation Method</b>	Floating   Glue Down   Nail

<b>Sqm/ Box</b>	2.904 m <sup>2</sup>
<b>Pieces / Box</b>	6 rows includes <20% nested
<b>Box / Pallet</b>	50
<b>Weight / Box</b>	28.31 kg

<b>Suitable Application</b>	Residential & Commercial
-----------------------------	--------------------------

### Performance & Safety Testing

<b>Slip (AS 4586-2013)</b>	P3 (SRV 39)
<b>Fire (AS ISO 9239.1-2003)</b>	3.9 kW/m <sup>2</sup>
<b>Acoustic Outcome</b>	L'nTw 40 (Homestead 5 mm rubber)
<b>AAAC Rating</b>	6 Star

Reports are available upon request.



Serein  
LET-1501




Wyn  
LET-1502



Auer  
LET-1503



Caldu  
LET-1504



Fika  
LET-1505




Maes  
LET-1506



Laine  
LET-1507



Ricci  
LET-1508



Toska  
LET-1509



Kohle  
LET-1510

Images are for general illustration only. Actual product colours may differ due to variations in screen displays or printing processes. The scale of the images does not reflect true colour variation. For an accurate representation, please refer to physical samples. Images are not legally binding.

## Technical Summary

<b>Grading</b>	ABCD
<b>Top Layer</b>	UV Cured Polyurethane Aluminium Oxide Coating
<b>Surface</b>	Pre-finished Matte Lacquer
<b>Finish</b>	Light Wire Brushed Texture
<b>Core Structure</b>	Plantation Eucalyptus/Birch Multi Cross Plywood
<b>Backing Layer</b>	Birchwood Veneer for extra stability
<b>Topcoat Adhesion</b>	4B   ASTM D3359
<b>Wear Resistance</b>	≥500 circles (S33 sand paper)   ASTM D4060
<b>Moisture Content</b>	6-9%
<b>Gloss Level</b>	6-8°
<b>Density</b>	754 kg/m <sup>3</sup>
<b>Janka Hardness Rating</b>	5.5-6.0 kN
<b>Formaldehyde Emission</b>	CARB Phase One ≤0.08 ppm   ASTM E1333
<b>Environmental</b>	Sourced from sustainable managed resources



### Durability

Up to 7 coats  
UV-hardened  
surface finish,  
consisting of  
polyurethane  
and aluminum  
oxide

### Wearability

Up to 6mm top  
layer in solid wood.

### Stability

Multiple cross  
plywood layers.



This specification data sheet has been prepared by National Select Floors. All information provided was accurate at the time of writing and publication. National Select Floors reserves the right to alter product details at any time without prior notification. Images included are for illustrative purposes only and do not confer any rights or guarantees.

National Select Floors recommends installation by a professional flooring contractor or skilled tradesperson and must follow the Australian Standards for flooring installations. All installations must also be performed in accordance with National Select Floors installation guidelines. If you have any concerns regarding the installation process, please contact your reseller.

Installation guidelines and Warranty information are available from our website.