

## SPECIFICATION DATA SHEET

The Natives range is a tribute to the enduring beauty of Australian hardwoods, engineered to embody timeless luxury with an understated elegance that lasts for generations. Featuring a 3 mm premium wear layer of authentic native species, it captures the classic appeal of natural timber while delivering exceptional durability.

Sustainably sourced from Australia's finest hardwoods, each plank radiates warmth, character, and strength, ensuring a product that is as responsible as it is refined.

The subtle matte brushing enhances the natural grain and texture, while multiple layers of UV cured lacquer provide advanced protection against stains and fading. Designed for longevity with minimal upkeep, the Natives range offers a floor that will remain as elegant and flawless as the day it was laid.

### Product Details

<b>Style</b>	Plank
<b>Timber Origins</b>	Australian Species
<b>Thickness / Wear Layer</b>	15 / 3 mm
<b>Board Size</b>	1900 x 190 mm
<b>Edge Profile</b>	Micro Bevelled
<b>Fitting System</b>	Tongue & Groove
<b>Installation Method</b>	Floating   Glue Down   Nail

<b>Sqm/ Box</b>	2.166 m <sup>2</sup>
<b>Pieces / Box</b>	6 rows includes <20% nested
<b>Box / Pallet</b>	50
<b>Weight / Box</b>	21.12 kg

<b>Suitable Application</b>	Residential & Commercial
-----------------------------	--------------------------

### Performance & Safety Testing

<b>Slip (AS 4586-2013)</b>	P3 (SRV 36)
<b>Fire (AS ISO 9239.1-2003)</b>	3 kW/m <sup>2</sup>
<b>Acoustic Outcome</b>	L'nTw 38 (Homestead 5 mm rubber)
<b>AAAC Rating</b>	6 Star

Reports are available upon request.



Blackbutt  
LET-1511



Spotted Gum  
LET-1512

Images are for general illustration only. Actual product colours may differ due to variations in screen displays or printing processes. The scale of the images does not reflect true colour variation. For an accurate representation, please refer to physical samples. Images are not legally binding.

## Technical Summary

<b>Grading</b>	ABCD
<b>Top Layer</b>	UV Cured Polyurethane Aluminium Oxide Coating
<b>Surface</b>	Pre-finished Matte Lacquer
<b>Finish</b>	Brushed Texture
<b>Core Structure</b>	Plantation Eucalyptus/Birch Multi Cross Plywood
<b>Backing Layer</b>	Birchwood Veneer for extra stability
<b>Topcoat Adhesion</b>	4B   ASTM D3359
<b>Wear Resistance</b>	≥500 circles (S33 sand paper)   ASTM D4060
<b>Moisture Content</b>	6-9%
<b>Gloss Level</b>	6-8°
<b>Density</b>	750 kg/m <sup>3</sup>
<b>Janka Hardness Rating</b>	5.5-6.0 kN
<b>Formaldehyde Emission</b>	CARB Phase One ≤0.08 ppm   ASTM E1333
<b>Environmental</b>	Sourced from sustainable managed resources

### Durability

Up to 7 coats  
UV-hardened  
surface finish,  
consisting of  
polyurethane  
and aluminum  
oxide

### Wearability

Up to 6mm top  
layer in solid wood.

### Stability

Multiple cross  
plywood layers.



This specification data sheet has been prepared by National Select Floors. All information provided was accurate at the time of writing and publication. National Select Floors reserves the right to alter product details at any time without prior notification. Images included are for illustrative purposes only and do not confer any rights or guarantees.

National Select Floors recommends installation by a professional flooring contractor or skilled tradesperson and must follow the Australian Standards for flooring installations. All installations must also be performed in accordance with National Select Floors installation guidelines. If you have any concerns regarding the installation process, please contact your reseller.

Installation guidelines and Warranty information are available from our website.