

SPECIFICATION DATA SHEET

The Medius range represents a refined interpretation of Lamella Engineered Timbers, where balanced proportions and considered detailing define its character. Crafted from premium European Oak, it presents a cleaner, more uniform aesthetic, creating a sophisticated foundation suited to both contemporary and classic interiors.

Engineered with a robust 15 mm profile and three layer solid wood construction, the Medius range delivers exceptional structural stability and long term performance. Its matte brushed surface enhances the natural elegance of the oak, while advanced UV-cured lacquer layers protect against everyday wear, staining, and fading; ensuring the floor maintains its refined appearance with minimal maintenance.

Available in a carefully curated palette of modern décors, the Medius range embodies elevated craftsmanship, enduring durability, and understated luxury; designed to bring clarity, balance, and timeless refinement to interior spaces.

Product Details


Style	Plank
Timber Origins	European Oak
Thickness / Wear Layer	15 / 3 mm
Board Size	1900 x 190 mm
Construction	Three Layer Solid
Fitting System	Tongue & Groove
Installation Method	Floating Glue Down
Sqm/ Box	2.166 m²
Pieces / Box	6 rows includes <20% nested
Box / Pallet	50
Weight / Box	17 kg

Suitable Application Residential & Commercial

Performance & Safety Testing

Slip (AS 4586-2013)	P3 (SRV 39)
Fire (AS ISO 9239.1-2003)	5 kW/m²
Acoustic Outcome	L'nTw 37 (Homestead 5 mm rubber)
AAAC Rating	6 Star


Reports are available upon request.



Images are for general illustration only. Actual product colours may differ due to variations in screen displays or printing processes. The scale of the images does not reflect true colour variation. For an accurate representation, please refer to physical samples. Images are not legally binding.

Technical Summary

Grading	Premium Grade
Top Layer	Solid European Oak
Core Board	Solid Hardwood Cross Lay
Bottom Layer	Solid Hardwood Veneer
Surface Finish	UV Cured Lacquer UV Oil
Surface Feel	Matte Brushed Texture
Edge Profile	Micro Bevelled
Wear Resistance	≥ 550 circles (S-33 wheels)
Moisture Content	6-9%
Janka Hardness Rating	5.5-6.0 kN
TVOC (C6-C16)	0.061 mg/m²/hr (ASTM D5116:2025)
Formaldehyde Emission	0.023 mg/m²/hr (ASTM D5116:2025)
Emission of PCP	≤ 5ppm
Environmental	Sourced from sustainable managed resources



This specification data sheet has been prepared by National Select Floors. All information provided was accurate at the time of writing and publication. National Select Floors reserves the right to alter product details at any time without prior notification. Images included are for illustrative purposes only and do not confer any rights or guarantees.

National Select Floors recommends installation by a professional flooring contractor or skilled tradesperson and must follow the Australian Standards for flooring installations. All installations must also be performed in accordance with National Select Floors installation guidelines. If you have any concerns regarding the installation process, please contact your reseller.

Installation guidelines and Warranty information are available from our website.